


999.00 EUR
incl. 19% VAT, plus [shipping](#)



- Applied Solid Capacitor for CPU VRM to ensure a longer lifespan for system
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- Dual Display design for multiple output support
- Integrated Printer (LPT) port / header to expand functionality
- Microsoft Windows 8 Certified
- Intel ® VRD 12 Ready
- Supports DirectX® 11 to enhance graphical performance
- Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function
- Free Bundle: CyberLink Media Suite

Supports Intel® CNVi

CPU	Onboard Intel® Bay Trail processors
	On-Board CPU Intel® Bay Trail J1900 processor
	VRD 12.0
	Solid Capacitor for CPU side
	Supports Intel® Hyper-Threading Technology
GRAPHICS	Supports DirectX® 11
	Supports Full HD 1080P Blu-ray / HD-DVD Playback
	Single-channel DDR3 Memory architecture
MEMORY	1 X DDR3 SO-DIMM socket
EXPANSION SLOT	Support up to 8 GB
Storage	1 X Mini PCI Express X1 slot(s) for Wi-Fi /Bluetooth modules
	2 X Serial ATAIII 3Gb/s
Audio	6-Channel HD audio CODEC Realtek ALC662
	Realtek ALC662 6-channel High Definition audio CODEC
	Meets performance requirements for Microsoft WLP 3.08 Vista premium and mobile PCs
	Six channel DAC supports 16/20/24-bit PCM format for 5.1 channel audio solution
	Emulation of 26 sound environments to enhance gaming experience
	Voice Cancellation and Key Shifting in Karaoke mode
	Compatible with Direct Sound 3D™, A3D™, I3DL2
	Realtek RTL8111G
	Gigabit Fast Ethernet Controller
	1 X USB3.1 Gen1 port(s) up to 5Gb/s
USB	8 X USB2.0 port(s) Up to 480 Mb/s (Back Panel 4 port(s), Onboard 4 port(s))

REAR PANEL I/O	1 X PS/2 Keyboard & PS/2 mouse connectors
	1 X Audio port (Line Out/Line In/Mic In)
	1 X RJ-45 port
	1 X HDMI port(s)
	1 X D-Sub (VGA) port(s)
	1 X USB3.1 Gen1 port(s)
	4 X USB2.0 port(s)
	1x DC-In connector
	1 X 4-pin CPU_FAN connector with smart fan
	1 X 4-pin SYS_FAN connector with smart fan
	1 X Front Panel MIC/Speaker out header
	1 X Front Panel switch/LED header
	1 X USB 2.0 header (Support additional 2 USB ports)
	2 X SATA II 3Gb/s connector(s)
	1 X CLR_CMOS header
CONNECTORS & HEADERS	2 X Serial port header (COM)
	1 X Parallel port header (LPT)
	1 X LVDS connector (optional)
	AMI BIOS with 8 MB SPI Flash ROM
	Supports ACPI 5.0 & DMI
	Dual Display Plug and Play, STR (S3) / STD (S4) , Hardware monitor, Multi Boot
	Multi-Language BIOS
	Audio, LAN, can be disabled in BIOS
	Dual-Monitor function
	Mini ITX Form Factor
	170*170
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
OS Support	Windows 10 64-bit
	Windows 10 32-bit
	CE/FCC Certification
	ErP/EuP Certification
Certifications	WHQL Certification
	WHCK Certification